



- TERRACOTTA
- UNPOLISHED STONE AND AGGLOMERATES



WHAT IT'S FOR

- A wet-look topical sealer product that protects outdoor and indoor surfaces in terracotta, unpolished natural stone and agglomerates.
- It protects surfaces against stains and dirt and is therefore the ideal product for use near kitchens, under barbecues and on driveways where cars are parked.

ADVANTAGES

- It enhances the material, giving a pleasing wet look.
- It is water based for more eco-friendly treatment and a drastic time saver because it can even be applied to surfaces with residual humidity.
- Highly resistant to light and heavy traffic.
- Weather resistant.
- The treated surface is easier to clean.
- **Very low VOC emission product:** certified by GEV and marked EC1 PLUS* and helps towards achieving credits for LEED**.

HOW IT'S USED

Ready to use: no dilution necessary
Application: Shake before use. Apply **FILAPT10** evenly to clean dry floors, using a large flat paintbrush, lambswool applicator pad or roller, working well into the grout joints. As this is a water-based product, it stands up to residual humidity and can therefore even be applied just a few days after initial washing. Apply a second coat of the product 2-3 hours later following the same method. Wait at least 12 hours before walking on the surface.
Maintenance: diluted **FILACLEANER** solution.

Warning: For surfaces with low absorption (slate, Botticino or Carrara marble) we recommend diluting the product with water (1 liter (1.06 qt) of product to 1 liter (1.06 qt) of water).
 Do not use on polished surfaces.
 Don't apply on smoothed surfaces.

COVERAGE

With one litre (1,06 QT):

Impruneta, rustic terracotta	15/20 m ² (161/215 sq ft)
Handmade or Spanish terracotta, flat tiles, bricks	7/10 m ² (75/107 sq ft)
Stone	10/20 m ² (107/215 sq ft)

*Coverage rates are approximate and refer to a single coat of the product"

Packaging

1 liter (1.06 qt) flasks in box of 12.
 5 liter (1.32 US gal) flasks in box of 4.

PRECAUTIONS

- Keep out of the reach of children.
- Dispose of the container properly after use.
- The product is not frost-proof in its can. To be treated, an external floor has to be laid perfectly, and respond to every requirement as, for example: the respect of slopes, the correct construction of joints, the perfect isolation of the floor and the tested frost resistance of the material.

TEMPERATURE

Storage temperature:
 between 41° F (5° C) and 86° F (30° C).
 Must be applied to material at temperatures between 50° F (10° C) and 86° F (30° C).

LABELLING

CAUTION: CAN IRRITATE EYES
 Keep Out of the Reach of Children. Contains alkalines. First Aid: In case of eye contact, rinse eyes with clean fresh water for up to 15 minutes. Get medical attention for irritation. Skin: Flush with running water. Remove contaminated clothing and wash before reuse. Seek medical advice if irritation develops. If swallowed, consult a physician or poison control center.

TECHNICAL INFORMATION

Appearance: liquid
Color: milky white
Odour: typical of resin
Density: 1.01 kg/litre
pH: 7.0

The information above reflects our latest technical know-how and is the outcome of ongoing laboratory research and testing. However, some factors are beyond our control. It is essential to integrate our suggestions with your own on-site preliminary tests and checks.
 Fila accepts no liability for improper use of its product