



### UNPOLISHED NATURAL STONES AND AGGLOMERATES



### WHAT IT'S FOR

- Pleasant wet look effect for rough-finish natural stone.
- Protects from water and oil.

### ADVANTAGES

- Wet-look effect can be increased with the number of coats applied.
- Certified as suitable for use on food contact surfaces.
- Does not yellow despite environmental conditions or ageing.
- Does not flake.

### HOW IT'S USED

**No dilution:** ready to use.

**Application:**

1. Apply an even, continuous coat of Filawet onto a clean and dry surface with brush or roller.
2. Wait 24 hours and then apply the second coat by the same method
3. For particularly porous materials, a third coat may be required to achieve the desired wet-look effect

**Maintenance:** diluted solution of FILACLEANER. In areas that are highly exposed to adverse atmospheric conditions it is advisable to repeat application every two years.

**Caution:**

Do not walk over the floor while it is drying. Wait 24 hours after application of the final coat. Do not apply to terracotta floors or polished surfaces. If the product has been applied incorrectly or if a thorough cleaning is required, use FILANOPAINT STAR. Do not apply this product outdoors if rain is in the forecast.

#### COVERAGE

With one litre (1,06 QT):

20 m<sup>2</sup> (215 sq ft)

"Coverage rates are approximate and refer to a single coat of the product"

### Packaging

1 liter (1.06 qt) flasks in box of 12.

#### PRECAUTIONS

- Keep out of the reach of children.
- Dispose of the container properly after use.
- When used indoors, ventilate the premises thoroughly.
- Avoid applying to very hot surfaces.

To be treated, an external floor has to be laid perfectly, and respond to every requirement as, for example: the respect of slopes, the correct construction of joints, the perfect isolation of the floor and the tested frost resistance of the material. Doesn't apply on surface very hot.

#### TEMPERATURE

Storage temperature: between 32° F (0° C) and 86° F (30° C). Must be applied to material at temperatures between 41° F (5° C) and 86° F (30° C).

#### LABELLING

DANGER! HARMFUL OR FATAL IF SWALLOWED. FLAMMABLE.

Contains petroleum distillates. Avoid frequent or prolonged contact with skin. Do not use near heat or open flame. If swallowed, call a poison control center, physician or emergency room immediately. Keep out of reach of children.

#### TECHNICAL INFORMATION

**Appearance:** transparent viscous liquid

**Odour:** typical aromatic solvent odour

**Density:** 0.908 kg/litre

**Flash point:** 104° F

The information above reflects our latest technical know-how and is the outcome of ongoing laboratory research and testing. However, some factors are beyond our control. It is essential to integrate our suggestions with your own on-site preliminary tests and check. Fila accepts no liability for improper use of its products.